



Perfect Door phone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. XonTel Video Door phone **XT-10P** enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- ✓ **Wide-angle camera: 120°**
- ✓ **PoE (IEEE802.3af, Power-over-Ethernet);**
- ✓ **Two-way audio communication over IP networks with Echo Cancel feature;**
- ✓ **Complies with SIP standard for easy integration in every SIP capable PBX;**
- ✓ **Complies with ONVIF standard for easy integration with any network surveillance system;**

XT-10P IP Video Outdoor Intercom



Physical & Power

Body material: Metal

Camera: 3M pixels, automatic lighting

Button: 1 call button

G-sensor: Support

Infrared Sensor: Support

RS485: Support

RF Card Reader: 13.56MHz & 125kHz

Output Relay: 2 output relays for door opener

802.3af Power-over-Ethernet

12V DC connector (if not using PoE)

Water-proof & Dust-proof: IP65

Installation: Wall-mounted

SIP Endpoint

SIP v1(RFC2543), SIP v2(RFC3261)

Audio codecs: G.711a, G.711μ, G.722, G.729

Video codecs: H.264

Speech Quality: 7kHz Audio

Echo Cancellation

Voice Activation Detection

Comfort Noise Generator

Video

Resolution: up to 720p

Maximum image transfer rate: 720p - 30fps

High intensity white LEDs for picture lighting during dark hours with internal light sensor

Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Features

Relays controlled individually by DTMF tones

Camera permanently operational

White balance: auto

Auto-night mode with LED illumination

Minimum illumination: 0.1LUX

Networking

1x10/100 Mbps Ethernet port

Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Application Scenarios

Office door phone with on-site or hosted IP-PBX

Remote site entry over Internet

Apartment/flat intercom with door access control

Temperature

Operating: -30 °C to +65 °C

Storing: -40 °C to +75 °C