



XT-10P IP Video Outdoor Intercom

Perfect Door phone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. **XonTel's** Video Door phone XT-10P enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- ✓ **Wide-angle camera: 120 °**
- ✓ **PoE (IEEE802.3af, Power-over-Ethernet);**
- ✓ **Two-way audio communication over IP networks with Echo Cancel feature;**
- ✓ **Complies with SIP standard for easy integration in every SIP capable PBXes;**
- ✓ **Complies with ONVIF standard for easy integration with any network surveillance system;**



Physical & Power

Body material: Metal
 Camera: 3M pixels, automatic lighting
 Button: 1 call button
 G-sensor: Support
 Infrared Sensor: Support
 RS485: Support
 RF Card Reader: 13.56MHz & 125kHz
 Output Relay: 2 output relays for door opener
 802.3af Power-over-Ethernet
 12V DC connector (if not using PoE)
 Water-proof & Dust-proof: IP65
 Installation: Wall-mounted

SIP Endpoint

SIP v1(RFC2543), SIP v2(RFC3261)
 Audio codecs: G.711a, G.711μ, G.722, G.729
 Video codecs: H.264
 Speech Quality: 7kHz Audio
 Echo Cancellation
 Voice Activation Detection
 Comfort Noise Generator

Video

Resolution: up to 720p

Maximum image transfer rate: 720p - 30fps

High intensity white LEDs for picture lighting during dark hours with internal light sensor

Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Features

Relays controlled individually by DTMF tones

Camera permanently operational

White balance: auto

Auto-night mode with LED illumination

Minimum illumination: 0.1LUX

Networking

1x10/100 Mbps Ethernet port

Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Application Scenarios

Office door phone with on-site or hosted IP-PBX

Remote site entry over Internet

Apartment/flat intercom with door access control

Temperature

Operating: -30 °C to +65 °C

Storing: -40 °C to +75 °C