



Premium touch screen for your home

The *XT-13P* multifunctional communicator, which works as an indoor monitor, provides audio and video communication with Door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7 inch capacitive touch screen display.

XT-13P IP Indoor Monitor



At a Glance

- Ultra clear, stylish appearance
- Thin profile and small footprint
- 7" capacitive touch screen with energy saving mode
- Reception of a HD picture from the door communicator
- Two-way communication with other units in the network, based on SIP v2.0 protocol
- Powered by PoE or external source
- Supports US or European electrical wall box mounting

Touch Screen Display

Display Type: Active matrix TFT, transmissive type

Size: 7 inch (176 mm) diagonal

Aspect Ratio: 16:9

Resolution: 800x480

Brightness: 200nits (cd/m²)

Contrast: 400:1

Color Depth: 18-bit, 0.26M colors

Illumination: Edge-lit LED

Viewing Angle: ±60° horizontal, ±70° vertical

Touch Screen: Projected Capacitive





Video

Streaming Formats: H.264

Audio

Features: Built-in microphone and speaker

Memory

RAM: 64MB Flash: 128MB

Communications

Ethernet: 2x10/100 Mbps ports, auto-switching, auto- discovery, auto-negotiating, full/half duplex, DHCP, IEEE 802.3af compliant

Environmental

Temperature: 14° to 112°F (-10° to 45°C) **Humidity:** 10% to 90% (non-condensing)

Mechanical parameters

Dimensions (W x H x D): 200 x 132 x 17.5 mm

Application Scenario

Villas
Apartment complexes
Home automation systems
Modern interiors

